

4091A

1U RF Autosense Fault Switch and Distribution Amplifier



4091A 1U RF Autosense Fault Switch and Distribution Amplifier

Key Features

- Redundant HOT SWAP power supplies
- 1-20 MHz operation
- Eight signal outputs
- Manual override
- Remote control via Ethernet

The 4091A is a 1U rackmount fault sense switch that accepts two RF inputs and produces eight outputs (chosen from the two inputs). The unit comes standard with a single HOT SWAP AC power supply and can be configuration with redundant HOT SWAP AC or DC power supplies. It has LED indicators that display the selected input as well as a control switch or place the switch in "auto" mode. When in "auto" mode, the unit automatically switches upon failure of the selected input. In addition to the front panel control, the unit can be controlled remotely via the Ethernet port on the rear of the unit.

4091A

Specifications

Unless otherwise stated, all specifications apply at 10 MHz, +13 dBm input level.

ELECTRICAL SPECIFICATIONS

- RF Input (2)
 - Frequency: 1–20 MHz
 - Level: 1 V RMS nominal into 50Ω
 - Connectors: BNC female
 - Control: Locking Toggle
- RF Output (8)
 - Connectors: BNC female
 - Gain: +0.5 +/- 0.5 dB
 - Harmonics: -40 dBc typ. at +13 dBm in
 - Spurious: <-80 dBc
- SSB Phase noise
 - 1 Hz -135 dBc
 - 10 Hz -145 dBc
 - 100 Hz -155 dBc
 - 1 kHz -163 dBc
 - 10 kHz+ -163 dBc
- Control & status
 - Switch between inputs
 - Set to autoswitch on input feature
 - Signal presence on all inputs and outputs
 - Green/Red LEDs on Front Panel
 - Network (RJ-45 connector)

ENVIRONMENTAL & PHYSICAL SPECIFICATIONS

- Temperature: 0°C to 40°C
- Humidity: 0 to 95% non-condensing
- Power requirements (AC Input): 90 – 264 V AC, 10 W, 47 – 63 Hz
- Dimensions: 1U [-1.75" / 4.44 cm] x 19" [48.26 cm] x 12" [30.48 cm]
- Weight: 12 lbs [5.40 kg]

OPTIONS

- Redundant AC Power Supply

The 4091A is for INDOOR USE ONLY. It is not sealed to prevent moisture from entering the enclosure. Equipment intended to be installed in an enclosed- or open-type equipment rack.

- Pollution Degree II per EN 61010-1
- Installation (Over-Voltage) Category II for transient over-voltages per EN 61010-1



Rear view



Microsemi Corporate Headquarters
 One Enterprise, Aliso Viejo, CA 92656 USA
 Within the USA: +1 [949] 380-6100
 Sales: +1 [949] 380-6136
 Fax: +1 [949] 215-4996

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor solutions for aerospace, defense and security; enterprise and communications; and industrial and alternative energy markets. Products include high-performance, high-reliability analog and RF devices, mixed signals and RF integrated circuits, customizable SoCs, FPGAs, and complete subsystems. Microsemi is headquartered in Aliso Viejo, Calif. Learn more at www.microsemi.com

©2014 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

DS/4091A/060314 900 00532 000B